



Care & Maintenance

BARRIER-GUARD

Congratulations on choosing Crossfield Products Corp. Membrane. Just follow the recommendations below to maximize the life of your Membrane System.

Cleaning

Membrane can be damaged by gouging or scraping with sharp objects and should be protected against such damage.

Maintenance

Membrane can be coated with a Cementitious protection coat during construction. This traffic topping is designed to withstand normal everyday wear and direct exposure to the elements when installed as per manufactures' application instructions.

Common Problems to Avoid

If damaged or worn through, apply additional membrane materials and water test.

In order to function properly, Membrane must "breathe".

Avoid heavy point loads being applied directly to the Membrane coating.

Do not expose the Membrane coating system to harsh chemicals or acids.

Do not subject the Membrane coating to continuous heavy rolling loads. Rolling loads will develop wear patterns, which will require re-coating cycles.

IMPORTANT NOTE: When working on equipment, ALWAYS use a protection boards to avoid laying or dropping parts or chemicals directly onto the Membrane installation.

Water test before encapsulating with over-layments, thin-set or mortar for tile.



DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office 3000 E. Harcourt Street Rancho Dominguez, CA 90221 310-886-9100 310-886-9119 fax	East Coast Office 140 Valley Road Roselle Park, NJ 07204 908-245-2800 908-245-0659 fax
--------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------

www.dexotex.com