



## Care & Maintenance

## CHEM-REZ N

## Chemical Resistant Flooring

Congratulations, on selecting the finest quality chemical resistant flooring available. Your new Dex-O-Tex Chem-Rez N chemical resistant seamless floor covering system will provide years of trouble free service with a minimum of maintenance. Just follow the recommendations below to maximize the performance and life of your floor covering.

### Cleaning

Cleaning your new Dex-O-Tex flooring is simple. Just wash with a mild cleaning solution such as "Simple Green" or "Ivory Liquid". Use a bristle to remove tough stubborn stains or residual compounds. Rinse thoroughly with clean water.

Regular cleaning will prevent build up of residue, which can make the floor surface slippery when wet.

### Maintenance

The Dex-O-Tex Chem-Rez N Chemical resistant flooring system incorporates Novolac epoxy technology, which provides tighter cross linking of the molecular structure of the polymeric resins base. The traffic topping is the only layer, which require ordinary maintenance.

The traffic topping is designed to withstand normal everyday wear and direct exposure to thermal and chemical elements. Harsh chemicals should be cleaned from the surface as soon as possible. Over a period of time the traffic topping needs to be resealed with Dex-O-Tex Chem-Rez topcoat sealer. This is required when traffic patterns become visible in the flooring.

This will be approximately 5 to 7 years in normal traffic areas and every 3 to 5 years in high traffic areas such as stairways and access corridors.

If your Dex-O-Tex flooring system becomes loose or debonded from the substrate for any reason call us or the installing contractor immediately. Any problem with the flooring system should be addressed immediately to prevent further damage.

### Common Problems to Avoid

Do not expose floor to temperatures in excess of 300° Fahrenheit. Do not allow water migration through any protrusions in the flooring system. Avoid standing water by properly designing a slope before application of the flooring system. Avoid heavy rolling loads with steel wheels. Floor areas subject to scratching by tracking of sand or grit from outside areas should be swept frequently.



### DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office  
3000 E. Harcourt Street  
Rancho Dominguez, CA  
90221  
310-886-9100  
310-886-9119 fax

East Coast Office  
140 Valley Road  
Roselle Park, NJ  
07204  
908-245-2800  
908-245-0659 fax



[www.dexotex.com](http://www.dexotex.com)