

Congratulations on selecting Dex-O-Tex Cheminert Flooring System. Just follow the recommendations below to maximize the life of your new surface.

Cleaning

Sweep or dry mop floor as required to remove all loose dirt, litter or foreign matter.

Maintenance

Periodically, as necessary, scrub floor with floor maintenance machine or scrubber-vac. Machine should mount a soft brush or scrubbing pad. Use neutral liquid detergent solution in strength as recommended by detergent manufacturer for resilient tile maintenance. When cleaning solution becomes dirty, discard it and mix a fresh solution. Hard to remove dirt, black heel marks, etc. should be rubbed gently with scrubbing pad wet with detergent solution.

Floor areas subject to scratching by tracking of sand or grit carried in from outside areas should be swept frequently.

Common Problems to Avoid

Promptly clean up all spills of liquid including oil, grease, etc. Promptly neutralize all acid or strong alkaline liquid spills as these may stain or physically damage flooring under prolong contact.

In the event of physical damage or after a prolong period of use it may be necessary to refinish the floor. If so, consult Crossfield Products Corp. or a Factory Trained Dex-O-Tex Contractor for detailed recommendations.



DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office
3000 E. Harcourt Street
Rancho Dominguez, CA
90221

310-886-9100
310-886-9119 fax

East Coast Office
140 Valley Road
Roselle Park, NJ
07204

908-245-2800
908-245-0659 fax

www.dexotex.com