

Congratulations on selecting Dex-O-Tex Gym-Flor Flooring System. Just follow the recommendations below to maximize the life of your new surface.

### Cleaning

Dry mop floor daily or as required with treated dust mop to remove all loose dirt, grit, litter or foreign matter. Wet mop as required to remove localized spillage of food substances, etc. Floor areas subject to scratching by trackage of sand or grit carried in from outside areas should be swept frequently.

### Maintenance

Periodically, as necessary, scrub floor with floor maintenance machine or scrubber-vac. Machine should mount a soft brush or scrubbing pad. Use neutral liquid detergent solution in strength as recommended by detergent manufacturer for resilient tile maintenance. When cleaning solution becomes dirty, discard it and mix a fresh solution. Hard to remove dirt, black heel marks, etc. should be rubbed gently with scrubbing pad wet with detergent solution.

A typical Dex-O-Tex Gym-Flor installation will give many months of service without refinishing. However, the floor should be checked periodically to see any evidence of wear-off of final coating. When this becomes apparent, contact a qualified Dex-O-Tex Factory Trained Applicator for refinishing recommendations.

### Common Problems to Avoid

Avoid cutting, gouging or scratching floor with sharp pointed metal objects. Folding tables, chairs and gymnastic equipment should be fitted with rubber-tipped legs. Metal volleyball net standards should be fitted with rubber protective pads. Roller skates should be fitted with urethane wheels and protective pads to prevent impact of sharp metal surfaces on the floor.

Do not roll heavy equipment such as pianos, net standards, etc. on floor unless equipped with rubber wheels of sufficient width to prevent indentation.

Do not permit rubber mats to remain on floor for long periods of time as certain types of mats may stain floor.

Avoid, if possible, applying game tape, line markings as these will eventually become difficult to remove without damaging the floor surface. However, if installed, remove such tape carefully by scraping with a blunt putty knife after dampening the tape with a rag soaked with mineral spirits.



### DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office  
3000 E. Harcourt Street  
Rancho Dominguez, CA  
90221  
310-886-9100  
310-886-9119 fax

East Coast Office  
140 Valley Road  
Roselle Park, NJ  
07204  
908-245-2800  
908-245-0659 fax

[www.dexotex.com](http://www.dexotex.com)