



Care & Maintenance

Congratulations, on selecting the finest quality chemical resistant flooring available. Your new Dex-O-Tex Posi-Tred CR chemical resistant seamless floor covering system will provide years of trouble free service with a minimum of maintenance. Just follow the recommendations below to maximize the performance and life of your floor covering.

Cleaning

Cleaning your new Dex-O-Tex floor is simple. Just wash with a mild solution such as "Simple Green" or "Ivory Liquid". Use a bristle brush to remove tough stubborn stains or residual compounds. Rinse thoroughly with clean water.

Regular cleaning will prevent build-up of residue, which can make the floor surface slippery when wet.

Maintenance

The Dex-O-Tex Posi-Tred CR Chemical Resistant Flooring System incorporates Novolac Epoxy Technology, which provides tighter cross linking of the molecular structure of the polymeric resins base. The traffic topping is the only layer, which requires ordinary maintenance.

The traffic topping is designed to withstand normal everyday wear and direct exposure to thermal and chemical elements. Harsh chemicals should be cleaned from the surface as soon as possible. Over a period of time the traffic patterns become visible in the flooring. This will be approximately 5 to 7 years in normal traffic areas and every 3 to 5 years in high traffic areas such as stairways and access corridors.

If your Dex-O-Tex flooring system becomes loose or de-bonded from the substrate for any reason call us or the installing contractor immediately. Any problem with the flooring should be addressed immediately to prevent further damage.

POSI-TRED CR Chemical Resistant Flooring

Common Problems to Avoid

Do not expose floor to temperatures in excess of 300° F.

Do not allow water migration through any protrusions in the flooring system.

Avoid standing water by properly designing slope before application of the flooring system

Avoid heavy rolling loads with steel wheels

Floor areas subject to scratching by tracking of sand or grit from outside areas should be swept frequently.



DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office
3000 E. Harcourt Street
Rancho Dominguez, CA
90221
310-886-9100
310-886-9119 fax

East Coast Office
140 Valley Road
Roselle Park, NJ
07204
908-245-2800
908-245-0659 fax

www.dexotex.com