

Congratulations on selecting the finest quality chemical and stain resistant urethane flooring available. Your new Dex-O-Tex Quik-Glaze Polyurea Topcoat will provide years of trouble free service with a minimum of maintenance. Just follow the recommendations below to maximize the life of your floor covering.

Cleaning

Cleaning your new Dex-O-Tex floor is simple. Just wash with cleaning solutions such as Dex-O-Tex Super Cleaner or "Simple Green" using recommended dilutions. Use a bristle brush to remove tough stubborn stains or residual compounds. Rinse thoroughly with clean water. Floor scrubbing machines, with soft brushes or non-abrasive pads, may be used for large areas.

Regular cleaning will prevent build-up of residue which can make the floor surface slippery when wet.

Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the system. As a precautionary step, Crossfield recommends that the end-user test their cleaning and disinfecting compounds on a sample or a small, out of the way finished area, utilizing the intended cleaning technique prior to cleaning the entire surface area. If no deleterious effects are observed, the procedure can be continued. If the cleaning and disinfecting compounds or cleaning techniques damage the system, modification of the cleaning material or techniques will be required. Contact your Representative for additional information.

Maintenance

The Dex-O-Tex Quik-Glaze Polyurea Topcoat consists of a specialized epoxy primer followed by topcoats of pigmented urethane resin. The system requires ordinary maintenance and is designed to withstand normal everyday wear and direct exposure to many chemicals and solvents. Over a period of time, traffic patterns or dull areas may become visible and it may be desirable to apply an additional coat of Quik-Glaze Topcoat. This will be approximately 5 to

7 years in normal traffic areas and every 3 to 5 years in heavy use or high traffic areas.

If your Dex-O-Tex Quik-Glaze flooring system becomes delaminated for any reason, call Crossfield Products Corp. or the installing contractor immediately. Any problem with the flooring system should be addressed immediately to prevent further damage.

Dex-O-Tex Quik-Glaze is best cleaned by scrubbing with a mild detergent solution to remove stains or residues, and clean water rinse. If resealing is required, lightly abrade the surface to break the gloss and produce a fine surface profile. Prepare the surface to be clean, dry and free from any contaminants. Apply Primer and Quik-Glaze with a rubber squeegee and backroll with a 1/8" mohair roller cover to achieve a smooth even finish.

Common Problems to Avoid

Floor areas subject to scratching by tracking of sand or grit carried in from outside areas should be swept frequently.

- Seal all punctures or protrusions through the flooring system.
- Resealing of the flooring system when required will dramatically increase the life of the flooring system.
- Avoid standing water by properly designing slope before application of the flooring system.
- Promptly clean up all spillage of harsh chemicals, acids or caustics.
- Avoid rolling loads with steel wheels.



DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office
3000 E. Harcourt Street
Rancho Dominguez, CA
90221
310-886-9100
310-886-9119 fax

East Coast
140 Valley Road
Roselle Park, NJ
07204
908-245-2800
908-245-0659 fax

www.dexotex.com