



## Care & Maintenance

## WALL-COTE E

Congratulations for choosing Wall-Cote E. Just follow the recommendations below to maximize the performance and life of your wall covering.

### Cleaning

Cleaning your new Wall-Cote E is simple. To remove dry dust, vacuum wall with vacuum cleaner with appropriate filter. To remove soil, wash wall with extension handle mop using detergent/germicidal cleaner. Remove germicidal residue with clear water wipe down.

### Maintenance

Hard to remove dirt, marks, etc. should be gently rubbed with scrubbing pad wetted with detergent solution. Do not use harsh abrasive pads.

### Common Problems to Avoid

Avoid gouging wall with sharp metal objects. Apply bumper pads on rolling carts to keep them away from walls.

Promptly remove all acid or strong alkaline spills on wall as these may stain or physically damage wall coating.

In the event of physical damage or after a prolonged period of use it may be necessary to refinish the wall. If so, consult Crossfield Products Corp. or a Factory Trained Dex-O-Tex Contractor for detailed recommendations.



### DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office  
3000 E. Harcourt Street  
Rancho Dominguez, CA  
90221

310-886-9100  
310-886-9119 fax

East Coast Office  
140 Valley Road  
Roselle Park, NJ  
07204

908-245-2800  
908-245-0659 fax

[www.dexotex.com](http://www.dexotex.com)