

DEX-O-TEX

Product Description Sheet

High Strength Mortar

Cementitious Mortar
Typical Thickness 1/16" – 2"



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

DESCRIPTION

High Strength Mortar is a single component, polymer-modified, pre-blended cementitious mortar fortified with micro-fiber reinforcement and shrinkage-compensating additives to achieve exceptional physical properties with very low drying shrinkage.

WHERE TO USE

- Interior and exterior, in wet or dry applications.
- Concrete surface repairs and flooring underlayment.
- Wall rendering and floor sloping mortar.

ADVANTAGES

- Interior or exterior applications
- Where a quick return to service is necessary
- Over 2,000 psi is achieved in 4 hours
- Low water absorption and drying shrinkage
- Excellent compressive, flexural and tensile strengths
- Great adhesion to prepared substrates
- Meets requirements of ANSI A 108.1

FINISH OPTIONS

Color: Grey

PHYSICALS	METHOD	RESULTS	
Compressive Strength	ASTM C109	4 Hour	2,225 psi
		1 Day	3,175 psi
		7 Day	5,575 psi
		28 Day	6,125 psi
Tensile Strength	ASTM C109	7 Day	435 psi
		28 Day	585 psi
Flexural Strength	ASTM C348	7 Day	845 psi
		28 Day	1,400 psi
Shrinkage	ASTM C157	<.04%	
Adhesion	ACI 503.R	>290 psi	
Initial Set	ASTM C 191	31 min	
Final Set	ASTM C191	39 min	

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

**Crossfield
Products Corp.**

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210)888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Installed by Factory Trained Dex-O-Tex Applicators Only

L-145
10-03-18

CARE AND MAINTENANCE

See care and maintenance form at www.dexotex.com

CHEMICAL RESISTANCE

See chemical resistance chart at www.dexotex.com

LIMITATIONS

- Concrete surface repair dimensions including overall length, width, depth and shape need careful consideration, and should be in conformance with ACI recommended standards of practice.
- Extension with coarse aggregates may alter the physical properties of *Dex-O-Tex High Strength Mortar* as published.
- Do not use solvent based curing compounds.
- As with all cement based materials, avoid direct contact with aluminum to prevent an adverse chemical reaction. Refer to *Dex-O-Tex VL Primer* for an appropriate primer.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210)888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.