

DEX-O-TEX

Product Description Sheet

A-81

Smooth, Sloping and Resurfacing Underlayment
Typical Thickness Feather Edge – 2"



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

L-56 04/19

DESCRIPTION

A-81 Underlayment is a polymer modified pre-packaged cementitious sloping, leveling and patching compound for structural or lightweight concrete or lath-reinforced plywood.

WHERE TO USE

A-81 Underlayment can be applied to any thickness from near featheredge upwards to the required thickness. It can be used on interior or exterior surfaces, including those exposed to freeze thaw.

It is designed for use beneath Dex-O-Tex surfacing material or as a sloping, smoothing, patching and resurfacing material. A-81 can be used as a smoothing underlayment prior to placement of carpet, resilient or ceramic tiles, rubber, vinyl or wood flooring and resinous floors. It is totally VOC compliant and contains no organic solvents. It is non-toxic and has only a slight odor during placement and cure.

A-81 SQ is also available and can be used over a wide range of substrates and for use under virtually any finished flooring or coating.

ADVANTAGES

- Superior adhesion.
- Low permeability, yet breathable.
- Interior-exterior Use
- Recommended for use with Dex-O-Tex floors and decks.
- Fast setting.
- Excellent freeze-thaw resistance.
- Similar expansion-contraction as concrete

PHYSICALS	METHOD	RESULTS
Compressive Strength	ASTM C109	4,140 psi
Tensile Strength	ASTM C307	800 psi
Flexural Strength	ASTM C580	1,200 psi
Hardness	ASTM D2240, Shore D	70-75
Adhesion	ASTM D4541	>400 psi
Water Absorption	MIL-D-3134 Para 4.7.1.4	3.14%

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Installed by Factory Trained Dex-O-Tex Applicators Only

LIMITATIONS

- Minimum ambient and surface temperatures should be 45°F (7°C) at time of placement and cure. Do not allow product to freeze prior to cure.
- If applied in direct hot sun or high winds, cover with curing blankets to minimize or prevent surface checking.
- A waterproofing and crack isolation membrane can be installed prior to system applications.
- Moisture vapor emission rates (MVER) in excess of 6.0lbs/1000 sq./ft/per 24hr. period per ASTM F1869, or an RH in excess of 78% per ASTM F2170 may result in delamination, discoloration or improper curing without proper treatment prior to installation of the flooring system. Consult with Crossfield Products Corp. for specific recommendations.
- VaporControl primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.