

DEX-O-TEX

Product Description Sheet

Cheminert Terrazzo

Thin-Set Epoxy Terrazzo
Typical Thickness 1/4" – 3/4" (6.35 mm – 19.06 mm)



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

L-150 07/19

DESCRIPTION

Cheminert Terrazzo flooring is a thin-set epoxy terrazzo flooring system, which incorporates marble chip or other decorative aggregates. Cheminert Terrazzo meets or exceeds the NTMA (National Terrazzo and Mosaic Association) and TTMAC (Terrazzo, Tile and Marble Association of Canada) Standards.

WHERE TO USE

Cheminert Terrazzo is conventionally used in high traffic commercial and institutional facilities that require a decorative flooring system with a design life of 40 to 50 years, such as airport terminals, shopping malls, schools, universities, churches, correctional facilities, corridors, convention centers or pharmaceutical manufacturing..

ADVANTAGES

- High durability
- Abrasion resistant
- Thin-section, light-weight
- Monolithic, including integral base
- California Department of Public Health 01350 Certified
- No toxic odors during installation
- Skid-resistant
- Low burning rate and negligible smoke production.

FINISH OPTIONS

Color: See Terrazzo Color Palette, [click here](#), at www.dexotex.com

PHYSICALS	METHOD	RESULTS
VOC in g/L	EPA METHOD 24	0 g/L
Percent Solids		
Compressive Strength	ASTM C109	12,000 psi
Surface Hardness	ASTM D2240 Shore D	80-85
Tensile Strength	ASTM C190	3,400 psi
Flash Point	ASTM D92	143° F
Water Absorption	MIL-D-3134	0.3%
Bond Strength	ACI 503.1	525 psi
Impact Resistance	MIL-D-3134 Para 3.15	Indentation 0.005 in.
Critical Radiant Flux		>1.07 Watts/CM ²
Flammability	ASTM D635	Self Extinguishing
Abrasion Resistance	ASTM D4060	0.07 gm
Microbial Resistance	ASTM G21	Passes Rating 1

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Crossfield
Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Installed by Factory Trained Dex-O-Tex Applicators Only

CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at www.dexotex.com

LIMITATIONS

- If concrete sub-surface cracks, Dex-O-Tex Cheminert Terrazzo may reflect these cracks to some degree.
- It is water repellent but not waterproof, however a waterproofing and crack isolation membrane can be installed prior to system application.
- Moisture vapor emission rates (MVER) in excess of 3.0 lbs/1000sq/ft/per 24hr. period per ASTM F1869, or in excess of 75% per ASTM F2170 may result in delamination, discoloration or improper curing without proper treatment prior to installation of the flooring system. Consult Crossfield Products Corp. for specific recommendations.
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.