

DEX-O-TEX

Product Description Sheet



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

Crossfield
Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Tek-Crete TT

Trowel Type - Urethane Concrete
Typical Thickness 1/4" to 3/8"

DESCRIPTION

Tek-Crete TT is a troweled urethane mortar flooring system, it provides superior performance in heavy abusive conditions including thermal cycling, chemical exposure, high heat.

WHERE TO USE

Typically used in rugged, tough and/or demanding service conditions. Complies with all USDA and FDA requirements for handling food, beverages, juice, spirits and wine in processing or preparation environments.

ADVANTAGES

- Durability: withstands heavy and abusive service
- Excellent chemical resistance
- Temperature resistance from -40°F (-40°C) up to 350°F (176°C)
- Environmentally friendly, low odor during installation and cure
- Minimal Down-Time: rapid cure and rapid return to service
- Moisture tolerant and slip resistant
- Tek-Crete anti-microbial additive
- LEED credit points may be available

APPROVALS

CDPH Certificate: Tek-Crete TT [click here](#)

FINISH OPTIONS

Color: Red, Grey, and Neutral

Finish: Monolithic

PHYSICALS	METHOD	RESULTS
Solids Content	ASTM D2369	>99%
VOC in g/L		< 0 g/L
Compressive Strength	ASTM C579	6,000 psi
Tensile Strength	ASTM C307	1,080 psi
Hardness	ASTM D2240	85-90
Thermal Coefficient of Linear Expansion	ASTM C531	1.1×10^{-5}
Density	ASTM C905 Lbs/ft ³	130 lbs/ft ³
Water Absorption	Mil-D-3134	0.64%
Flammability	ASTM E648	>1.07 watts/cm ²
Adhesion	ASTM D4541	>400 psi
Microbial Resistance	ASTM G21	Passes

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Page 1

File Code L-191

2-19

Installed by Factory Trained Dex-O-Tex Applicators Only

Tek-Crete TT

Trowel Type - Urethane Concrete
Typical Thickness 1/4" to 3/8"

CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at www.dexotex.com

CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at www.dexotex.com

LIMITATIONS

- Not recommended for use over flexible substrates, which may include plywood, wood, flexible diamond plate, flexible wall panels, etc.
- Surface imperfections such as pinholes or surface asperities may appear on the surface.
- Possible discoloration under extreme UV exposure.
- Sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.
- **Caution:** Extremely porous substrates can require a primer coat.

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210)888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800