

DEX-O-TEX

Product Description Sheet



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

04-20

Crossfield
Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Weatherwear

Promenade Deck and Roof Covering
Typical Thickness 3/16" – 1/4"

DESCRIPTION


Weatherwear promenade and roof deck covering system is a class A rated, multi-layered troweled applied waterproofing and wearing surface.

WHERE TO USE

Exterior decking, roof tops, balconies, promenade decks.

ADVANTAGES

- Monolithic, Seamless and Jointless
- Integral Flashing Slip Sheet Design isolates building movement
- Excellent UV Stability
- Low Maintenance
- Environmentally Friendly
- VOC Compliant
- Class A Fire Rated
- Over 100 million sq. ft installed since 1958
- Solar Reflective Topcoat available



APPROVALS

- ICC ESR 1757 ([click here](#))

FINISH OPTIONS

See Dexotex AJ-44 XL and Colorpax LIP Color chart ([click here](#)) or at www.dexotex.com

PHYSICALS	METHOD	RESULTS
VOC in g/L		0.50 g / L
Weight / sq. ft.		1.65 - 2.2 lbs / sq. ft (depends on thickness)
Fire Safety	ASTM E108	Intermittent Flame Exposure - Class A
	UL 790	Spread of Flame - Class A
	NFPA 256	Burning Brand - Class A
Accelerated Weathering	ASTM G23	No Cracking, Blistering, Caulking, Crazing, or Color Change
Freeze Thaw	ASTM C67 (50 cycles)	No Breakage, weight loss >1%
Percolation	ICC A39	Complies
Water Absorption	ASTM D570	6.09%
Wind Uplift	ICC A 39 (131 mph)	Complies
Microbial Resistance	ASTM G21	Passes Rating 1
Sound Rating STC	ASTM E413	53
Sound Rating IIC	ASTM E492	47

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Installed by Factory Trained Dex-O-Tex Applicators Only

CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at www.dexotex.com

CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at www.dexotex.com

LIMITATIONS

- Substrate must be dry during application residual moisture content of substrate must be less than 15%
- Not suitable for uses when subject to heavy steel wheel rolling loads
- Can be damaged by moisture vapor entering from adjacent areas not properly sealed
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield products Corp. for specific recommendations

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.