

DEX-O-TEX

Product Description Sheet



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

10/20

**Crossfield
Products Corp.**

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Terracolor

Decorative Aggregate Floor
Typical Thickness 3/16" – 1/4"

DESCRIPTION

Terracolor is a thin-section, trowel applied, decorative flooring system, designed to produce a seamless floor and cove base.

WHERE TO USE

- Pharmaceutical Manufacturing Plants
- Research and Development Facilities
- Education Facilities
- Medical Facilities
- Operating Suites and Emergency Rooms
- Restrooms and Locker Rooms
- Institutional Facilities

ADVANTAGES

- Monolithic, including cove base
- Chemical Resistance
- Decorative Finish
- Easily maintained
- Hard Surface For High Traffic Areas
- Anti-Microbial additive available

FINISH OPTIONS

- See Terracolor color chart, [click here](#), or at www.dexotex.com

APPROVALS

- CDPH 1350 Certificate, [click here](#), or at www.dexotex.com

PHYSICALS	METHOD	RESULTS
VOC in g/L		0 g /L
Compressive Strength	ASTM D 695	10,000 psi
Tensile Strength	ASTM C307	1,400 psi
Flexural Strength	ASTM C580	4,000 psi
Surface Hardness	ASTM D2240, Shore D	80-85
Adhesion	ASTM D4541	>400 psi
Flammability	ASTM D635	Self extinguishing by this test
Abrasion Resistance	ASTM D4060	0.04 gr
Microbial Resistance	ASTM G21	Passes Rating 1

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Installed by Factory Trained Dex-O-Tex Applicators Only

CARE AND MAINTENANCE

See Care and Maintenance, [click here](#), or available at www.dexotex.com

CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at www.dexotex.com

LIMITATIONS

- Discoloration may occur under UV exposure, use Dex-O-Tex Quik-Glaze where UV stability is required.
- Cracking of substrate may reflect through flooring system (Crack isolation membrane will reduce this possibility).
- May be incorporated with a Dex-O-Tex Waterproof or crack isolation membrane.
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost
- Moisture vapor emission rates (MVER) in excess of 10 lbs/1000 sq/ft/per 24 hr. period per ASTM F1869, or an RH in excess of 84% per ASTM F2170 requires the application of Dex-O-Tex Vapor Control 1P epoxy moisture mitigation primer.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.