

DEX-O-TEX

Product Description Sheet



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

11/20

Crossfield
Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Quik-Glaze FC

Polyurea Topcoat
Typical Thickness 7-15 mils

DESCRIPTION

Dex-O-Tex Quik-Glaze FC (Fast Cure) is a state of the art, high solids, and UV stable, aliphatic polyurea.

WHERE TO USE

Some typical floor applications include: Cold storage areas, food service preparation areas, beverage service areas, decorative entry foyers, high traffic areas, promenade decks, labs, pharmaceutical production, and areas exposed to chemical use

ADVANTAGES

- Fast Cure
- High Elongation
- High tear strength
- Excellent UV resistance
- Excellent abrasion resistance
- Chemical resistant
- High Gloss finish
- CDPH 1350 approval
- Antimicrobial additive available

FINISH OPTIONS

See Standard Epoxy and Urethane Color Chart L-334 [click here](#) or available at www.dexotex.com
Also available in Clear Gloss, Satin, and custom colors.

PHYSICALS	METHOD	RESULTS
VOC in g/L	40 CRF 60 appendix A7 Method 24	Clear 93 g /L Pigmented 86 g /L
Percent Solids		95%
Tear Strength	ASTM D624, Die C	879 lbs. / in
Taber Abrasion	ASTM D4060	33 mg loss
Impact Resistance	ASTM D2794	160 in / lbs.
Tensile Strength	ASTM D412	2,400 psi
Flexibility	ASTM D1737	passes
Hardness	ASTM D2240 Shore A	85-90
Gloss	ASTM D523	90+ for Clear Gloss
Coefficient of Friction	ASTM D2047	0.67 dry & 0.82 wet
Microbial Resistance	ASTM G21	Passes Rating 1
Chemical Resistance		See chemical resistance chart

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Installed by Factory Trained Dex-O-Tex Applicators Only

CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at www.dexotex.com

CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at www.dexotex.com

LIMITATIONS

- If sub-surface cracks move due to continued thermal flexing or mechanical loads or building settlement, Dex-O-Tex Quik-Glaze FC may reflect those cracks to some degree.
- Dex-O-Tex SC Membrane may be used as a waterproofing and crack isolation membrane prior to system application.
- Moisture vapor emission rates (MVER) in excess of 10 lbs/1000 sq/ft/per 24 hr period per ASTM F1869, or an rh in excess of 84% per ASTM F2170 requires the application of Vapor Control 1P.
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.