

DEX-O-TEX

Product Description Sheet



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

12/20

Barrier Guard

Waterproof Membrane
Typical Thickness 25-40 MILS

DESCRIPTION

Barrier-Guard Waterproofing Membrane is an exceptional copolymer emulsion waterproofing designed for use beneath ceramic tile, marble, quarry tile, below grade and between slab, and under most Dex-O-Tex composition floor and deck systems.

WHERE TO USE

Typically used as a waterproof membrane under Dex-O-Tex cementitious and decking systems.

ADVANTAGES

- Provides positive side waterproofing
- Unlike waterproofing sheet goods, fluid applied membranes can easily be applied over irregular shapes
- Forms monolithic tightly adhering membrane across floors and up bases/curbs
- Environmentally safe
- No organic solvents
- IAPMO certified as an ANSI 118.18 shower pan liner

FINISH OPTIONS

- ~~Barrier Guard Membrane is not an exposed finished flooring system~~

PHYSICALS	METHOD	RESULTS
VOC in g/L	40 CFR 60, Appendix A-7, method 24	9 g/L
Tensile Strength	ASTM D638	345 psi
Elongation	ASTM D638	580%
Adhesion to Peel Concrete	ASTM C794	8.3 lbs.
Crack Bridging	ASTM C836, 1/8" opening	No rupture
Hydrostatic Resistance	ASTM D751	Passes
Permeability	ASTM E96	0.013 gr / in
Flammability	ASTM E648	>1.07 watts/cm ²
Microbial Resistance	ASTM G21	Passes Rating 2

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Installed by Factory Trained Dex-O-Tex Applicators Only

CARE AND MAINTENANCE

Only applicable for the final flooring finish selected over the Barrier Guard.

CHEMICAL RESISTANCE

Only applicable for the final flooring finish selected over the Barrier Guard.

LIMITATIONS

- Concrete substrate must be sound and durable and free of large "working" cracks to prevent reflection through finish.
- Moisture vapor emission rates (MVER) in excess of 3 lbs/1000 sq/ft/per 24 hr period per ASTM F1869, or an RH in excess of 78% per ASTM F2170 may result in delamination, discoloration or improper curing without proper treatment prior to installation of the flooring system. Consult with Crossfield Products Corp. for specific recommendations.
- VaporControl primers, sloping, smoothing or leveling compounds, crack repair or isolation, or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.
- Not recommended for application over expansion joints or seismic joints.
- All loose or unsound concrete must be removed and repaired.
- Do not allow product to freeze before cure.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210)888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.