

DEX-O-TEX

Product Description Sheet



Advanced Floor
and Waterproof
Systems since
1938

www.dexotex.com

11/20

Crossfield
Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

Cheminert K

Troweled Epoxy Floor

Typical Thickness 3/16" to 1/4" Industrial Floor with Integral Cove Base

DESCRIPTION

Cheminert K is a troweled seamless epoxy industrial flooring system comprised of a specially formulated two-component epoxy resin, specially engineered aggregates, and top coat.

WHERE TO USE

- Industrial Facilities
- Machine stops
- Warehouses
- Food processing and Manufacturing areas
- Commercial freezers

ADVANTAGES

- Monolithic with integral cove base
- Renew surface deteriorated floors
- High compressive strength
- Anti-Microbial properties
- Excellent abrasion and impact resistance
- Chemical resistant
- Produces a rapidly installed seamless troweled floor system
- Low temperature stability
- CDPH 1350 Approval
- Wide variety of engineered topcoats available
- Installed only by Professional Factory Trained Dex-O-Tex Contractor

PHYSICALS	METHOD	RESULTS
VOC in g/L		3 g / L
Compressive Strength	ASTM C579	10,000 psi
Compressive Strength	ASTM D695	11,000 psi
Tensile Strength	ASTM C307	1,640 psi
Tensile Strength	ASTM D638	4,000 psi
Flexural Strength	ASTM C580	4,300 psi
Bond Strength	ASTM D4541	100% concrete failure
Abrasion Resistance	ASTM D4060	0.04 gr
Water Absorption	MIL-D-3134	0.3%
Surface Hardness	ASTM D2240 Shore D	80-85
Microbial Resistance	ASTM G21	Passes Rating 1

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

Installed by Factory Trained Dex-O-Tex Applicators Only

CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at www.dexotex.com

CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at www.dexotex.com

LIMITATIONS

- Discoloration may occur under UV exposure, use Dex-O-Tex Quik-Glaze or other Dex-O-Tex UV stable topcoats
- If substrate movement takes place due to deflection or building settlement, Cheminert K may reflect those cracks to some degree.
- Dex-O-Tex SC Membrane may be used as a waterproofing and crack isolation membrane prior to system application.
- Moisture vapor emission rates (MVER) in excess of 3.0 lbs./1000 sq. ft./per 24 hour period per ASTM F1869, or an RH in excess of 78% per ASTM F2170 may require the installation of an appropriate Vapor Control Moisture Mitigation system. Consult with Crossfield Products Corp. for specific recommendations.
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.

Crossfield Products Corp.

California
3000 E. Harcourt St.
Rancho Dominguez,
90221
(310) 886-9100

Texas
128 Industrial Dr.
Cibolo, 78108
(210) 888-0449

New Jersey
140 Valley Rd.
Roselle Park, 07204
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.