

# DEX-O-TEX

## Product Description Sheet



Advanced Floor  
and Waterproof  
Systems since  
1938

[www.dexotex.com](http://www.dexotex.com)

11/20

Crossfield  
Products Corp.

California  
3000 E. Harcourt St.  
Rancho Dominguez,  
90221  
(310) 886-9100

Texas  
128 Industrial Dr.  
Cibolo, 78108  
(210) 888-0449

New Jersey  
140 Valley Rd.  
Roselle Park, 07204  
(908) 245-2800

## Colorflake

Decorative Flake Floor with Integral Cove Base  
Typical Thickness 1/16" – 1/8"

### DESCRIPTION

Dex-O-Tex Colorflake is a seamless, fluid-applied, double broadcast, epoxy flooring system consisting of an epoxy primer basecoat, epoxy receiving coat, which is broadcast with decorative vinyl chips, and followed by a clear topcoat .

### WHERE TO USE

Intended use for commercial, industrial and institutional areas, such as manufacturing, processing, warehousing, stairs, ramps, walkways, locker rooms, hallways, bathrooms, corridors and commons-areas.

### ADVANTAGES

- Water clear epoxy
- Wide range of attractive flake blends available
- Low VOC
- Skid resistant
- Can be applied over a wide range of surfaces and applications
- No significant odor during installation
- Resists most common chemical spillage
- Installed only by Factory Trained Contractors
- Anti-microbial additive available
- LEED Points may be available

### FINISH OPTIONS

See Décor Flor Colorflake Color Chart, [click here](#), or available at [www.dexotex.com](http://www.dexotex.com)

Optional Topcoats: Décor Flor, Quik-Glaze, Posi-Tred CR (Clear Amber), HPT, Aero-Flor 100

PHYSICALS	METHOD	RESULTS
VOC in g/L	40 CRF 60 appendix A7 Method 24	2 g / L
Percent Solids		100%
Compressive Strength	ASTM D695	9,000 psi
Tensile Strength	ASTM D638	1,200 psi
Hardness	ASTM D2240 Shore D	80-85
Adhesion	ASTM D4541	100% concrete failure
Flexibility	ASTM D1737	180° bend, 3/4" mandrel
Flammability	ASTM D635	Self-extinguishing bonded to concrete
Water Absorption	MIL-D-3134	<1.0%
Microbial Resistance (with additive)	ASTM G21	Passes Rating 1
Chemical Resistance	See chemical resistance chart	

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

*Installed by Factory Trained Dex-O-Tex Applicators Only*

## CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at [www.dexotex.com](http://www.dexotex.com)

## CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at [www.dexotex.com](http://www.dexotex.com)

## LIMITATIONS

- If sub-surface cracks move due to continued thermal flexing or mechanical loads or building settlement, Dex-O-Tex Colorflake Broadcast System may reflect those cracks to some degree.
- Dex-O-Tex SC Membrane may be used as a waterproofing and crack isolation membrane prior to system application.
- Discoloration may occur under UV or chemical exposure. For UV stability use Quik-Glaze Topcoat.
- Moisture vapor emission rates (MVER) in excess of 3 lbs./1000 sq/ft/per 24 hr. period per ASTM F1869, or an RH in excess of 75%% per ASTM F2170 requires the application of Vapor Control Primers
- Vapor control primers, sloping, smoothing or leveling compounds, crack repair or isolation, waterproof membranes or other supplementary items may be required for proper installation at an additional cost. Consult with Crossfield Products Corp. for specific recommendations.

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.

### **Crossfield Products Corp.**

**California**  
3000 E. Harcourt St.  
Rancho Dominguez,  
90221  
(310) 886-9100

**Texas**  
128 Industrial Dr.  
Cibolo, 78108  
(210) 888-0449

**New Jersey**  
140 Valley Rd.  
Roselle Park, 07204  
(908) 245-2800