

# DEX-O-TEX

## Product Description Sheet



Advanced Floor  
and Waterproof  
Systems since  
1938

[www.dexotex.com](http://www.dexotex.com)

1/21

Crossfield  
Products Corp.

California  
3000 E. Harcourt St.  
Rancho Dominguez,  
90221  
(310) 886-9100

Texas  
128 Industrial Dr.  
Cibolo, 78108  
(210) 888-0449

New Jersey  
140 Valley Rd.  
Roselle Park, 07204  
(908) 245-2800

## Dex-Flex

Waterproof Deck System  
Typical Thickness 1/8" - 1/4"

### DESCRIPTION

Dex-Flex waterproof deck system is a solvent-free, fluid applied, elastomeric waterproofing and polyacrylate pedestrian traffic topping system that is ideal for concrete or plywood substrates.

### WHERE TO USE

Dex-Flex is ideal for promenade decks, sun decks, patios, roofs, rooftop tennis courts, balconies, and pedestrian traffic surfacing.

### ADVANTAGES

- Monolithic, including integral flashing
- Resilient and comfortable underfoot
- Reduces sound transmission
- Environmentally safe
- Monolithic, seamless
- Fast cure time and return to service
- Solvent free with minimal odor
- VOC and LEED compliant

### FINISH OPTIONS

- See AJ 44 and Colorpax LIP Color Chart available at [www.dexotex.com](http://www.dexotex.com)
- Wide array of slip resistant textures, colors, and finishes available

PHYSICALS	METHOD	RESULTS
VOC in g/L		0 g / L
Weight		2.5 lbs. per sq ft
Tensile Elongation	ASTM D638	65%
Tensile Strength	ASTM D638	750 psi
Waterproofness	Resistance to passage when subjected to 27.7" head of water	
Permeability		0.75 perm / inches
Microbial Resistance	ASTM G21	Passes Rating 1
Salt Spray	ASTM B117	No Degradation
Freeze-Thaw	ASTM D67	Weight loss < 1%

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

*Installed by Factory Trained Dex-O-Tex Applicators Only*

## CARE AND MAINTENANCE

See care and maintenance form, [click here](#), or available at [www.dexotex.com](http://www.dexotex.com)

## CHEMICAL RESISTANCE

See chemical resistance chart, [click here](#), or available at [www.dexotex.com](http://www.dexotex.com)

## LIMITATIONS

- Substrates must be dry when material is applied.
- For Concrete Substrates, Moisture vapor emission rates (MVER) in excess of 3lbs/1000 sq/ft/per 24 hr. period per ASTM F1869, or an RH in excess of 70% per ASTM F2170 requires the application of A Dex-O-Tex VaporControl Primer
- Plywood must be 5/8" minimum supported floor joists 16" on center.

### **Crossfield Products Corp.**

**California**  
3000 E. Harcourt St.  
Rancho Dominguez,  
90221  
(310) 886-9100

**Texas**  
128 Industrial Dr.  
Cibolo, 78108  
(210) 888-0449

**New Jersey**  
140 Valley Rd.  
Roselle Park, 07204  
(908) 245-2800

LIMITED WARRANTY NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICE ARE MET. Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield examination shall disclose to Crossfield's satisfaction to be thus defective. IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION, ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIALS NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCT OR PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES. CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.