



# DEX-O-TEX

## Product Description Sheet

### HPT

High-Performance Polyurethane Topcoat  
Typical Thickness 3-5 MILS

Advanced Floor  
and Waterproof  
Systems since  
1938

[www.dexotex.com](http://www.dexotex.com)

4/21

#### DESCRIPTION

Dex-O-Tex HPT is a uniquely versatile High-Performance Polyurethane topcoat using the latest technology of polyurethane resin systems.

#### WHERE TO USE

Typically used for laboratories, hospitals, pharmaceutical manufacturing, and high traffic areas.

#### ADVANTAGES

- Low Odor During Application
- Low VOC Content
- High Chemical Resistance
- UV Stable
- Excellent Cleanability
- Superior Gloss Retention
- Abrasion Resistance

#### FINISH OPTIONS

Color: High Clear Gloss, White, Grey  
Finish: Slip Resistance Additive Available

PHYSICALS	METHOD	RESULTS
Solids Content	ASTM D2369	52%
VOC in g/L		<50g/L
Impact Resistance	ASTM D 2794 Direct	160 in/lbs
	ASTM D 27943 Reverse	160 in/lbs
Pot Life	70 DF 50% RH	45 minutes
Gloss	ASTM D237	85+
Tensile Strength	ASTM D2370	5,000 psi
Elongation	ASTM 2370	4%
Abrasion Resistance	ASTM D4060 (1,000 cycles, CS-17 wheel)	15 mg/loss

The above physical properties were measured in accordance with the referenced standards. Results may vary based upon statistical variations on mixing methods and equipment, application methods, environment, and actual site conditions and curing conditions. All sample preparation and testing are conducted in a laboratory environment and actual performance on job site may vary from these values based on actual site conditions.

#### CARE AND MAINTENANCE & CHEMICAL RESISTANCE

Information can be found at [www.dexotex.com](http://www.dexotex.com)

#### WARRANTY

All sales are subject to the Crossfield Terms and Conditions effective on the date the purchase order is received. The Terms and Conditions are incorporated herein in full by this reference. The Terms and Conditions are set forth at ([www.dexotex.com](http://www.dexotex.com)) and will also be sent by mail or fax to the purchaser upon request. By placing an order, the Buyer acknowledges that it has read and agrees to the provisions of the Terms and Conditions.

*Installed by Factory Trained Dex-O-Tex Applicators Only*

Crossfield  
Products Corp.

California  
3000 E. Harcourt St.  
Rancho Dominguez,  
90221  
(310) 886-9100

Texas  
128 Industrial Dr.  
Cibolo, 78108  
(210) 888-0449

New Jersey  
140 Valley Rd.  
Roselle Park, 07204  
(908) 245-2800